

sealing for a safer and greener tomorrow

## **Product information**

# TEADIT 24 HD

REV2013345

#### Material properties:

TEADIT 24 HD is a non-asbestos gasket material made from expanded, pre-densified, pure virgin PTFE. The whole production process is subject to strict quality control, registered under DIN EN ISO 9001

#### **Application areas:**

**TEADIT 24 HD** is particularly well suited to compensate for out-of-parallel and/or damaged sealing surfaces, and where a certain remaining thickness is required. Typical applications are heat exchangers, large containers, tank lids, pump housings, flanges, hand- and manholes, etc.


#### **Technical data:**

- Temperature range: 240°C up to +260°C, for short periods up to +310°C
- Chemical resistance: resistant against all chemicals from pH 0-14 (except molten alkali metals and elemental fluorine at high temperature and pressure)
- Pressure resistance: vacuum up to 200 bar
- Density: 1,0 g/cm3, +/- 0,1g/cm3
- Aging resistance: **TEADIT 24 HD** does not age (please note: adhesive tape has limited shelf life!)
- · Colour: white

### Advantages:

- Quick and simple installation: adhesive strip makes installation easier
- Excellent malleability: compensates for small damages and uneven areas on the flange faces
- Exceptional thermal and chemical stability: makes this material very versatile
- No risk: the versatility of **Teadit 24 HD** eliminates the risk of using wrong material for a certain application this prevents avoidable breakdowns
- TEADIT 24 HD is physiologically harmless. It has no smell or taste. It is neither contaminating nor toxic and does not get influenced by micro-organisms and / or fungi.





### Standard dimensions:

Dimensions (mm)	Standard flange size				
• 4 x 2,5	up to DN 500				
• 6 x 4,6	from DN 500 up to DN 1500				
• 8 x 5,5	DN 1500 and larger				
• 10 x 7	DN 1500 and larger				

When choosing the best suitable dimension of **TEADIT 24 HD**, one has to take the available bolt torque and possibly damaged or out-of-parallel gasket surfaces into account.

**TEADIT 24 HD** is available on spools, with self-adhesive strip

#### Approvals: • WRc



WILLIAM JOHNSTON & COMPANY LIMITED Glasgow: 0141 620 1666 Inverness: 01463 238673

re to select the correct materials or products we supply (The Products") may result in damage to plant, equipment or property, in some instances, it may cause death or person designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific cularly where critical conditions exist, we will fry to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical cog the specifications of the different Products which we supply. To the extent permitted in law, no warrantly is given in respect of any information supplied by us. The customer selves as to the suitability of the Products which we supply. To the extent permitted in law, no warrantly is given in respect of any information supplied by us. The customer selves as to the suitability of the Products which we supply. To the extent permitted in law, no warrantly is given in respect of any information supplied by us. The customer selves as to the suitability of the Products which we supply of to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by ou in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by ou



width mm	thickness 0,3 mm	thickness 0,7 mm	thickness 2,5 mm	thickness 4,6 mm	thickness 5,5 mm	thickness 6,0 mm	thickness 7,0 mm	
3,2	Х	Х						
4,0			x					
6,0				x				
8,0					x			
10,0							х	
15,0						x		

