



WILLIAM JOHNSTON & COMPANY LIMITED

Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673
sales@williamjohnston.co.uk | www.williamjohnston.co.uk

Black Closed Cell EPDM/Neoprene - WJSP320



Requirement / Specification	Specification Limits	Typical Value
Size - skin / skin (mm)	2000 x 1000 x 54 (±4)	
Compression @ 25% Deflection (kPa) ASTM D1056-00	35 - 65	43
Compression Deflection @ 50% (kPa) ASTM D1056-00	80 - 160	112
Density (kg/M ³) ISO 845-95	120 ± 20	122
Compression Set (50%22h20°C) ASTM D1056-00	25% Max.	19.1%
Water absorption, max. change in weight (%) ASTM D1056-00	10	0.8
Heat Ageing, Change in Compression Deflection, 168 hrs @ 70°C	± 30%	Pass
Flammability FMVSS 302	Burn Rate < 100mm	Pass
Flammability UL94 HBF		Pass
Elongation at Break (%) ISO 1798-7	N/A	>180
Tensile Strength (KN/M ²) ISO 1798-7	N/A	> 500
Temperature Range (Low - High)	N/A	-40 TO + 85 °C
High Intermittent	N/A	+100 °C.
Resistance to Air + UV		Excellent
Resistance to Oil		Poor
Resistance to Acids		Good
Environmental Protection		CFC and HFC free / Can be recycled
Specification	ASTM D1056-00 AFNOR 99-211	2A2 B2C 2C08/3C08 B3 C2

This material passes the 3C08 requirements but the majority polymer is EPDM

Change Control Date	Change
30/07/2013	Created

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.