



## Product information

REV202111

# Stuffing-Box-Packing Type 2017/Z

### Description

Diagonally braided from gPTFE-yarn (PTFE with incorporated graphite), reinforced throughout its body with continuous Aramid yarn, lubricated with silicone oil.

### Properties

Style 2017/Z is a high performance multi-yarn packing which combines the advantages of the supple gPTFE material with those of tough and durable Aramid. This results in reduced shaft-wear and better thermal conductivity than standard Aramid packings.

### Application areas

Multi-purpose packing for use with rotary- and piston-pumps, mixers, stirrers, reactors, for industrial and chemical process valves, suitable for high pressure applications.

### Application media

Style 2017/Z can be used with a wide variety of media including abrasive ones: cold and hot water, steam, solvents, oils, greases, diluted acids and lyes, brine, sewage, etc.

### Not suitable for

Concentrated acids and lyes, alkali metals, fluorine and fluorine compounds at high temperatures, oxygen.

### Benefits

TEADIT style 2017/Z is particularly suited for difficult sealing applications as with high pressures or abrasive media, such ensuring longer service life. Combines exceptional extrusion resistance and high mechanical strength with good chemical and thermal stability.



Temperature:

|      |        |        |
|------|--------|--------|
|      | - temp | + temp |
| (°C) | 100    | 280    |

Pressure:

|       |           |                |         |
|-------|-----------|----------------|---------|
|       | rotating: | reciprocating: | static: |
| (bar) | 30        | 50             | 200     |

pH: 2-12    density: (g/cm<sup>3</sup>) 1,6    v: (m/s) 15

#### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.