



## Product information

REV202111

# Stuffing-Box-Packing Type 2044

### Description

Diagonally braided from high-grade aramid staple fibre yarn, impregnated throughout with PTFE and a silicone-free lubricant.

### Properties

Very dense packing for high pressure and high speed applications, excellent replacement for PTFE-impregnated asbestos packings, particularly well suited for use with abrasive media.

### Application areas

For pumps, valves, sliders, agitators, etc., in most industries where a strong and durable packing is required.

### Application media

Water, steam, oils, lubricants, diluted acids and lyes, abrasive media, paints and varnishes, solvents, gases, etc.

### Not suitable for

Highly concentrated acids and lyes, a few organic compounds, alkali metals.

We recommend a shaft (sleeve) hardness  $\geq 60$  HRC.

### Benefits

Hard wearing and economical packing for a wide range of applications in many different industries.



#### Temperature:

	- temp	+ temp
(°C)	100	280

#### Pressure:

	rotating:	reciprocating:	static:
(bar)	20	80	150

pH: 2-12    density: (g/cm<sup>3</sup>) 1,45    v: (m/s) 15

#### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.