



## Product information

REV202111

# Stuffing-Box-Packing Type 2202

## Description

TEADIT Packing style 2202 is diagonally braided from pure expanded flexible graphite, reinforced at the corners with a high quality pure carbon yarn.

## Properties

TEADIT style 2202 is the newest generation of graphite packings, specifically designed for very demanding applications. Because of the special construction style 2202 can be used in areas where normal expanded graphite packings fail.

The pure carbon fibres reinforcing the corners and body of this packing, make style 2202 at least three times more resistant to extrusion and also extremely pressure resistant.

## Application areas

This unique and extremely versatile packing can be used in all demanding applications, both static and dynamic. Style 2202 does not suffer from limitations that prevent general service use in both pumps and valves.

It is extremely well suited for high temperature - high pressure installations occurring in power stations, petrochemical plants, steel mills etc.

## Application media

Although designed with an eye on high temperature steam applications, style 2202 can be used with all chemicals but the most aggressive acids. Very good all-purpose packing which can lower stock volumes considerably.

## Not suitable for

Strong oxidizing agents

## Benefits

Style 2202 lacks the stiffness of conventional carbon or graphite packings. Because of the high proportion of expanded flexible graphite TEADIT style 2202 conforms readily to stuffing box configurations, installs easily and requires little gland adjustments.

Excellent extrusion resistance.

## Fire-Safe certificate



### Temperature:

	- temp	+ temp	steam:
(°C)	240	450	650

### Pressure:

	rotating:	reciprocating:	static:
(bar)	30	200	300

pH: 0-14 density: (g/cm<sup>3</sup>) 1,1 v: (m/s) 20

### Approval:

- Fire-Safe

### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.